

AA00242-0003652892	MATERIAL SAFETY DATA SHEET	Date of Issue	20220117
3652892		Renewal Date	20230728
Page 1 / 8		Renewal No.	1

1. CHEMICAL PRODUCT INFORMATION

Product Name	C01LX5100 PCCL-0064-0T 0799	Color	0799
Application	PRINT CLEAR 8. Coatings and paints, thinners, paints removers 8.1 Oil paint		
Manufacture	SAMHWA PAINTS IND.CO.,LTD.	Telephone NO.	82-31- 499 - 0394
Address	178, Byeolmang-ro, Danwon-gu, Ansan-si, Gyeonggi-do, Korea	Department	

2. HAZARDS IDENTIFICATION

1. Classification of the substance

- ① FLAMMABLE LIQUIDS - category 3
- ② ASPIRATION HAZARD - category 1
- ③ CARCINOGENICITY - category 1B
- ④ GERM CELL MUTAGENICITY - category 1B
- ⑤ ACUTE TOXICITY (ORAL) - category 2
- ⑥ ACUTE TOXICITY (INHALATION-VAPOR) - category 3
- ⑦ HAZARDOUS TO THE AQUATIC ENVIRONMENT(CHRONIC HAZARD) - chronic 2

2. GHS warning label elements, including precautionary statements

① Symbol :



② Signal word : Danger

③ Hazard statements : Toxic if inhaled

May cause cancer(state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard)

Flammable liquid and vapor

May be fatal if swallowed and enters airways

Toxic to aquatic life with long lasting effects

Fatal if swallowed

May cause hereditary defects(state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard)

④ Precautionary statements :

Prevention- Do not handle until all safety precautions have been read and understood.

Wash...thoroughly after handling.

Avoid breathing dust/fume/gas/mist/vapours/spray.

Use explosion-proof[electrical/ventilating/lighting]equipment.

Obtain special instructions before use.

Wear protective gloves/protective clothing/eye protection/face protection/hearing protection/...

Use only outdoors or in a wellventilated area.

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking

Keep container tightly closed.

Ground and bond container and receiving equipment

Use non-sparking tools.

Take precautionary measures against static discharge.

Do not eat, drink or smoke when using this product.

Avoid release to the environment.

Response- Do NOT induce vomiting.

Call a POISON CENTER or doctor/physician.

IF exposed or concerned: Get medical advice/attention.

IF ON SKIN(or hair) : Take off immediately all contaminated clothing. Rinse affected areas with water [or shower].

AA00242-0003652892	MATERIAL SAFETY DATA SHEET	Date of Issue	20220117
3652892		Renewal Date	20230728
Page 2 / 8		Renewal No.	1

④ Precautionary statements :

- Response- Specific treatment (see on this label).
Collect spillage.
Rinse mouth.
IF INHALED : Remove person to fresh air and keep comfortable for breathing.
In case of fire: Use Suitable extinguishing media for extinction.(Refer Section MSDS 5)
IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.
- Storage- Store in a well-ventilated place. KEEP cool.
Store in a well-ventilated place. Keep container tightly closed.
Store locked up.
- Disposal- Dispose of contents/container to relate laws and regulations.

3.CHEMICAL COMPOSITION

Chemical Name	CAS NO.	Portion(%)	Remarks
2-Methyl-2-propenoic acid methyl ester homopolymer	9011-14-7	More than 1 ~ Under 10 %	
Methylated 1,3,5-triazine-2,4,6-triamine, formaldehyde polymer	68002-20-0	More than 1 ~ Under 10 %	
2-Propanol	67-63-0	More than 0.1 ~ Under 1 %	
Solvent naphtha (petroleum), light arom.	64742-95-6	More than 1 ~ Under 10 %	
Solvent naphtha (petroleum), heavy arom.	64742-94-5	More than 11 ~ Under 20 %	
Trimethylolpropane-neopentyl glycol-1,6-hexanediol-phthalic anhydride-adipic acid copolymer	64385-79-1	More than 41 ~ Under 50 %	
Hexanedioic acid dimethyl ester	627-93-0	More than 1 ~ Under 10 %	
Silicon dioxide	112926-00-8	More than 1 ~ Under 10 %	
Pentanedioic acid, dimethyl ester	1119-40-0	More than 1 ~ Under 10 %	
Butanedioic acid dimethyl ester	106-65-0	More than 1 ~ Under 10 %	
Isobutylacrylate	106-63-8	More than 0.1 ~ Under 1 %	

4.HEALTH HAZARD INFORMATION

- Eye contact
Wash off immediately with plenty of water, also under the eyelids, for at least 20 minutes.
Call a physician immediately.
- Skin contact
Remove the contaminated clothes and the skin will be washed with water and soap.
Do not use solvents.
- Inhalation

AA00242-0003652892	MATERIAL SAFETY DATA SHEET	Date of Issue	20220117
3652892		Renewal Date	20230728
Page 3 / 8		Renewal No.	1

4.HEALTH HAZARD INFORMATION

Move to fresh air and if he/she not breathes perform artificial respiration.

Consult a physician if necessary.

4. Ingestion

Do not induce vomiting unless it is indicated by medical personnel.

Never give anything by oral tract to an unconscious. Get medical attention if symptoms appear.

5. Note to physician

Very small quantities of the product reached in lungs may be fatale. Ingestion of the product may cause chemical irritation that may diffuse to lungs and cause edema. Check carefully the victim and apply intubations in all ingestion cases for all important amounts.

5.FIRE FIGHTING MEASURES

1. Flash point : 55 °C

2. Ignition temp : Not determined

3. Upper expollosion limit / Lower explosion limit : Not determined

4. The Fire Service Act : Fourth grade 2nd.Petroleum

5. Fire extinguisher : CO2, Powder, Halogen Fire extinguisher and Sand etc.

6. Fire and explosion Method of extinguishing and equipment:

Wear suitable protective equipment Use product with caution around heat, sparks, pilot lights, static electricity, and open flame.

Due to vapor is heavier than air, keep the distance from the ignition source pour into the fresh air.

Remove promptly flammable material. Put out a fire at once with prepared fire extinguisher.

7. Hazardous materials in combustion:

Could be generated complexed mixture like solid and gas containing CO, SO2 etc.

Unidentified organic and inorganic compound.

8. Extinguishing method which must not used for safety : Not applicable

6.ACCIDENTAL RELEASE MEASURES

1. Personal precautions

Evacuate useless personnel, isolate the heat and flame sources, ventilate and wet the area if is possible.

All personnel must be protected against vapours inhalation and against skin and eyes contact.

2. Methods for cleaning up

Absorb with dry earth, sand or other non-combustible material and precede according decontamination regulation.

Recovered product will be stored in metallic drums with removable lid or metallic containers, which will be sent to incineration.

3. Environmental precautions

Do not let the product to reach water, drain and earth. Prevent the extending in soil.

Prevent entry into sewers, basements or confined areas; dike if needed

7.HANDLING AND STORAGE

1. Handling

Avoid contact with skin or eyes. Use only up well-ventilated areas.

Avoid breathing vapor. Do not take internally. Take precautionary measures against static is charges.

2. Storage

The product must be kept in original container tightly closed. Store between 5~35°C in dry, well-ventilated place away from source of heat, ignition and direct sunlight.

Solvent vapours are heavier than air and spread along floors. Vapours may form explosive mixtures. No smoking.

3. Other precautions

Emergency showers and eye wash stations should be readily accessible.

AA00242-0003652892	MATERIAL SAFETY DATA SHEET	Date of Issue	20220117
3652892		Renewal Date	20230728
Page 4 / 8		Renewal No.	1

7. HANDLING AND STORAGE

Adhere to work practice rules established by government regulations

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

1. Exposure limit values

Chemical Name	Cas No	Interior provision	ACGIH
2-Methyl-2-propenoic acid methyl ester homopolymer	9011-14-7	No data	No data
Methylated 1,3,5-triazine-2,4,6-triamine, formaldehyde polymer	68002-20-0	No data	No data
2-Propanol	67-63-0	TWA : 200 ppm 480 mg/m ³ STEL : 400 ppm 980 mg/m ³	STEL 400 ppm TWA 200 ppm
Solvent naphtha (petroleum), light arom.	64742-95-6	No data	No data
Solvent naphtha (petroleum), heavy arom.	64742-94-5	No data	No data
Trimethylolpropane-neopentyl glycol-1,6-hexanediol-phthalic anhydride-adipic acid copolymer	64385-79-1	No data	No data
Hexanedioic acid dimethyl ester	627-93-0	No data	No data
Silicon dioxide	112926-00-8	TWA : 10 mg/m ³	No data
Pentanedioic acid, dimethyl ester	1119-40-0	No data	No data
Butanedioic acid dimethyl ester	106-65-0	No data	No data
Isobutylacrylate	106-63-8	No data	No data

2. Environmental exposure control

Technical conditions regarding atmosphere protection. Determination of pollutants emission produced by stationary sources rules.

3. Respiratory protection: In case of insufficient ventilation, wear suitable respiratory equipment

4. Eye protection: Wear eye/face protection such as chemical goggles or face shield

5. Hand protection: For prolonged or repeated contact use solvent protective gloves. Barrier reams may help to protect the exposed areas of hand. However they should not be applied once exposure has occurred. Hand should be washed after contact

6. Skin protection: Personnel should wear protective clothing and antistatic footwear.

7. Additional: Before eating, drinking, or smoking, wash face and hands thoroughly with soap and water

AA00242-0003652892	MATERIAL SAFETY DATA SHEET	Date of Issue	20220117
3652892		Renewal Date	20230728
Page 5 / 8		Renewal No.	1

9. PHYSICAL AND CHEMICAL PROPERTIES

- | | |
|--|-------------------------------------|
| 1. Appearance : colored and transparent liquid | 8. Oxidising properties : No data |
| 2. Odor : solvent specific | 9. Vapor pressure : No data |
| 3. pH : Not applicable | 10. Specific gravity : 1.073 |
| 4. Solubility : Water-insoluble | 11. Partition coefficient : No data |
| 5. Boiling point : No data | 12. Vapor density : No data |
| 6. Melting point : No data | 13. Viscosity(25℃) : 100±10 |
| 7. Explosive properties : No data | 14. Molecular weight : No data |

10. STABILITY AND REACTIVITY

- Chemical stability
The product is stable if is kept in original recipient and according with recommendation.
- Condition to avoid
Avoid all possible sources of heat, electrostatic discharges, ignition(spark or flame).
Avoid storage at temperature higher than 35℃ and direct exposure in the sunlight.
- Materials to avoid
Strong oxidative substances, strong acid, and alkaline solutions may give exothermic reactions in contact with this product.
- Hazardous decomposition products
Thermo oxidative decomposition gives carbon monoxide, carbon dioxide, nitrogen oxides and a dense smoke, which contain other unidentified decomposition products. If this product is heated up to its decomposition temperature may lead to explosion.

11. TOXICOLOGICAL INFORMATION

1. Toxicity Information

Chemical Name	LD50.Oral	LD50.Skin	LD50.Inhalation (gas)	LD50.Inhalation (vapour)	LD50.Inhalation (mist)
2-Methyl-2-propenoic acid methyl ester homopolymer	No data	No data	No data	No data	No data
Methylated 1,3,5-triazine-2,4,6-triamine, formaldehyde polymer	LD50 12.3 ml/kg Rat	No data	No data	No data	No data
2-Propanol	LD50 = 4710mg/kg Rat	LD50 = 12870 mg/kg rabbit	해당없음	LC50 = 72600 mg/ℓ 4 hr Rat	해당없음
Solvent naphtha (petroleum), light arom.	LD50 = 8400 mg/kg Rat	LD50 > 2000 mg/kg Rabbit	NO DATA	LC50 = 5.160 mg/ℓ 4 hr Rat	NO DATA
Solvent naphtha (petroleum), heavy arom.	LD50 > 5000 mg/kg Rat	LD50 > 2000 mg/kg Rabbit	NO DATA	NO DATA	NO DATA
Trimethylolpropane-neopentyl glycol-1,6-hexanediol-phthalic anhydride-adipic acid copolymer	No data	No data	No data	No data	No data
Hexanedioic acid dimethyl ester	LD50 = 1920 mg/kg Rat	No data	No data	No data	No data

AA00242-0003652892	MATERIAL SAFETY DATA SHEET	Date of Issue	20220117
3652892		Renewal Date	20230728
Page 6 / 8		Renewal No.	1

11. TOXICOLOGICAL INFORMATION

1. Toxicity Information					
Chemical Name	LD50.Oral	LD50.Skin	LD50.Inhlation (gas)	LD50.Inhlation (vapour)	LD50.Inhlation (mist)
Silicon dioxide	LD50 = 3300 mg/kg (Species : not)	LD50 = 5000 mg/kg	Steam LC50 > 2.0 mg/ℓ Rat	Steam LC50 > 2.0 mg/ℓ Rat	Steam LC50 > 2.0 mg/ℓ Rat
Pentanedioic acid, dimethyl ester	LD50 = 1920 mg/kg Rat	LD50 = 8500 mg/kg Rat	해당없음	자료없음	해당없음
Butanedioic acid dimethyl ester	LD50 > 5000 mg/kg Rat	LD50 > 5000 mg/kg Rabbit	No data	No data	No data
Isobutylacrylate	LD50 = 4895 mg/kg Rat	LD50 = 800 mg/kg Rabbit	Steam LC50 = 10.59 mg/ℓ 4 hr Rat	Steam LC50 = 10.59 mg/ℓ 4 hr Rat	Steam LC50 = 10.59 mg/ℓ 4 hr

12. ECOLOGICAL INFORMATION

1. Ecological Information			
Chemical Name	LC50.fish	LC50.water fleas	LC50.algae
2-Methyl-2-propenoic acid methyl ester homopolymer	No data	No data	No data
Methylated 1,3,5-triazine-2,4,6-triamine, formaldehyde polymer	No data	No data	No data
2-Propanol	LC50 > 100 mg/ℓ 96 hr	자료없음	EC50 = 2.2 mg/ℓ 96 hr
Solvent naphtha (petroleum), light arom.	LC50 = 9.22 mg/ℓ 96 hr	EC50 = 6.14 mg/ℓ 48 hr Daphnia magna	EC50 = 19 mg/ℓ 72 hr
Solvent naphtha (petroleum), heavy arom.	LC50 = 45 mg/ℓ 96 hr Pimephales	EC50 = 0.95 mg/ℓ 48 hr Daphnia magna	EC50 = 2.5 mg/ℓ 72 hr
Trimethylolpropane-neopentyl glycol-1,6-hexanediol-phthalic anhydride-adipic acid copolymer	No data	No data	No data
Hexanedioic acid dimethyl ester	LC50 = 87.095 mg/ℓ 96 hr	No data	EC50 = 6.691 mg/ℓ 96 hr (No
Silicon dioxide	No data	No data	No data
Pentanedioic acid, dimethyl ester	LC50 = 13400 mg/ℓ 96 hr	EC50 = 3940 ~ 4670 mg/ℓ 48 hr Daphnia	No data
Butanedioic acid dimethyl ester	LC50 = 50 ~ 100 mg/ℓ 96 hr	LC50 = 3317.276 mg/ℓ 48 hr	EC50 = 11.917 mg/ℓ 96 hr

AA00242-0003652892	MATERIAL SAFETY DATA SHEET	Date of Issue	20220117
3652892		Renewal Date	20230728
Page 7 / 8		Renewal No.	1

12.ECOLOGICAL INFORMATION

1. Ecological Information

Chemical Name	LC50.fish	LC50.water fleas	LC50.algae
Isobutylacrylate	LC50 = 2.09 mg/ℓ 96 hr Pimephales	LC50 = 9.7 mg/ℓ 48 hr Daphnia magna	EC50 = 3.18 mg/ ℓ 72 hr

2. Soil mobility : Not known

3. Persistence and degradability

There is no specific data available on the product itself. The product should not be allowed to enter drains or watercourses or be deposited where they can affect ground or surface waters.

4. Potential bioaccumulation : Be possible.

13.DISPOSAL CONSIDERATION

1. Relevant insurance of legislation

Dispose of in accordance with local regulations

2. Waste removal measures

Waste must be disposed of in accordance with state and local environmental regulations.

3. Direction for the waste disposal

Preferred options for disposal are recycling, incineration with energy recovery, and landfill.

14.TRANSPORT INFORMATION

1. Classification by shipping transportaiton dangerous substance and regulation of storage :

2. Direction for transport

The product must be kept in original container tightly closed and transport at normal temperature.

3. International Martitie Dangerous Goods Code

U.N Number : 1263

Shipping name : PAINT (including paint, lacquer, enamel, stain, shellac, varnish, polish, liquid filler and liquid lacquerbase) or PAINT RELATED MATERIAL (including paint thinning or reducing compound)

Hazard class : 3

Packing group : 3

4. Marine pollutant : Applicable

5. Special precautions for user related to transport or transportation measures

● Ems FIRE SCHEDULE : F-E

● EmS SPILLAGE SCHEDULE : S-E

AA00242-0003652892	MATERIAL SAFETY DATA SHEET	Date of Issue	20220117
3652892		Renewal Date	20230728
Page 8 / 8		Renewal No.	1

15.REGULATORY INFORMATION

1. Article of KOREA OCCUPATIONAL SAFETY _HEALTHY AGENCY : Not determined. Water-insoluble
2. Article of Harmful Chemical Substance :
3. Classify of The Fire Service Act : Fourth grade 2nd.Petroleum

16.OTHER INFORMATION

The information provided in this Material Safety Data Sheet is correct to the best of our knowledge, information and belief at the data of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release is not to be considered a warranty or quality specification

The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

This information is based on technical information believed to be reliable. It is subject to revision as additional knowledge and experience is gained.